

**AXEON FSD Filtration Systems** feature a compact single, double or triple stage design and are available with 3/4" or 1" ports. These systems are ideal for water treatment applications that require additional pre or post treatment.

### FSD-100 Models Feature

- Two AXEON 0 – 100 Pressure Gauges
- One 4.5" Diameter Black and Blue Pentek® Filter Housing in 10" or 20" Lengths
- One White Powder Coated Bracket
- One Filter Housing Wrench

FSD-120 SERIES



### FSD-200 Models Feature

- Two AXEON 0 – 100 Pressure Gauges
- Two 4.5" Diameter Black and Blue Pentek® Housings in 10" or 20" Lengths
- One White Powder Coated Bracket
- One Filter Housing Wrench

FSD-220 SERIES



### FSD-300 Models Feature

- Two AXEON 0 – 100 Pressure Gauges
- Three 4.5" Diameter Black and Blue Filter Housings in 10" or 20" Lengths
- One White Powder Coated Bracket
- One Filter Housing Wrench

FSD-320 SERIES



## Benefits

- High Quality Components
- Accommodate Standard 4.5" Diameter Cartridges
- 1-Year Limited Warranty
- Customizable with Any Cartridge
- Pre-Assembled and Easy to Install
- Made in the U.S.A.

Engineered Water Treatment Solutions


# AXEON FSD Filtration Systems

## Product Specifications

Part Number	Description	Port Size	System Size
<b>FSD-100 SERIES</b>			
200086	FSD-110 Filtration System*	3/4" FNPT	8" x 7.5" x 17.5"
200087	FSD-110 Filtration System*	1" FNPT	8" x 7.5" x 17.5"
200088	FSD-120 Filtration System*	3/4" FNPT	8" x 7.5" x 27.5"
200089	FSD-120 Filtration System*	1" FNPT	8" x 7.5" x 27.5"
<b>FSD-200 SERIES</b>			
200090	FSD-210 Filtration System*	3/4" FNPT	8" x 15" x 17.5"
200091	FSD-210 Filtration System*	1" FNPT	8" x 15" x 17.5"
200092	FSD-220 Filtration System*	3/4" FNPT	8" x 15" x 27.5"
200093	FSD-220 Filtration System*	1" FNPT	8" x 15" x 27.5"
<b>FSD-300 SERIES</b>			
200094	FSD-310 Filtration System*	3/4" FNPT	8" x 22.5" x 17.5"
200095	FSD-310 Filtration System*	1" FNPT	8" x 22.5" x 17.5"
200096	FSD-320 Filtration System*	3/4" FNPT	8" x 22.5" x 27.5"
200097	FSD-320 Filtration System*	1" FNPT	8" x 22.5" x 27.5"

\* Cartridges Sold Separately

## Typical Installation Diagram for Water Filtration System



### Operating Specifications

Minimum Temperature: 40°F
Maximum Temperature: 100°F
Minimum Operating Pressure: 45 psi
Maximum Operating Pressure: 85 psi
Set pressure regulator to 75 psi

- \*\* Not to be installed outdoors or in areas exposed to extreme climate conditions.
- \*\* Pressure regulator highly recommended.